

Krete Control 230

Krete Control 230 is a non-swipe producing admixture designed to offer integral water repellency and both primary and secondary efflorescence control in semi dry concrete products.

FEATURES

- Water Repellency
- Efflorescence Control

BENEFITS

- Minimizes Water Penetration/Absorption
- Improves Service Life of CMUs
- Improves Aesthetic Appearance of CMUs
- Promotes and Maintains Brighter Colours

TECHNICAL INFORMATION

| Parameter | Typical Value |
|------------------|-----------------|
| Appearance | Clear Liquid |
| Specific Gravity | 0.900 |
| Solids, % | Not Established |
| IR | Pass |

DIRECTIONS FOR USE

1. Use at dosage rate 125 - 250ml per 100kg of cementitious material.
2. Add after the introduction of the pre-wet aggregates.
3. Mix for 90 seconds after addition of admixture.
4. Check the moisture content of the mix and add additional water if needed.

PRODUCT PACKAGING

Available in 1000 litre IBCs, 210 litre drums and 25 litre jerry cans. Samples are available by request.

PRODUCT STORAGE AND SHELF LIFE

Store in dry area. Keep containers tightly closed. Do not store in excessively high temperatures (>35 C°). KEEP FROM FREEZING. Avoid physical damage to containers.

Krete Control 230 has a rheological shelf life of eight (8) months in original, unopened packaging.

DESIGN AND CONSTRUCTION

Design and construction details and recommendations, included in NCMA TEK 19-01: Water Repellents for Concrete Masonry Walls; TEK 19-2B: Design for Dry-Single-Wythe Concrete Masonry Walls; TEK 19-5A: Flashing Details for Concrete Masonry Wall, and TEK 19-07: Characteristics of Concrete Masonry Units with Integral Water Repellents, must be observed and incorporated.

NOTE: Krete Control 230 must be used as a component of the CMU and Krete Gard Mortar Mix as a component of the mortar when a fully water repellent wall system is desired. Krete Control 230 and Krete Gard Mortar Mix are part of the "system" that provides moisture protection of concrete masonry walls. Proper masonry design and construction such as proper drainage within the core and cavity, properly installed through-wall flashing and weeps, and properly tooled joints are also critical requirements..

The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.

PDS - Control 230 - 01/2016

*For Industrial Use Only.
Not for internal consumption.
Consult SDS for safety and regulatory information.*





CONCRETE

PRODUCT DATA SHEET DRY CAST

Krete Control 230

Krete Control 230 is a non-swipe producing admixture designed to offer integral water repellency and both primary and secondary efflorescence control in semi dry concrete products.

Data Sheet continued

PRODUCT TESTING

Masonry units containing Krete Control 230 have been successfully tested according to the following specifications:

- ASTM E514 - Standard Test Method for Water Penetration and Leakage Through Masonry.
- ASTM C140 - Standard Test Method for Sampling and Testing Concrete Masonry Units and Related Units.

The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.

PDS - Control 230 - 01/2016

*For Industrial Use Only.
Not for internal consumption.
Consult SDS for safety and regulatory information.*

 **krete**[®]
THE CONCRETE CHOICE IN ADMIXTURES

Excelsior Works Castle Park Flint Flintshire CH6 5NT United Kingdom
T +44 (0) 1352 732 157 F +44 (0) 1352 735 530 E info@procterjohnson.com
procterjohnson.com

 **ProcterJohnson**

Krete Control 230

Krete Control 230 is a non-swipe producing admixture designed to offer integral water repellency and both primary and secondary efflorescence control in precast concrete products at low dosage rates.

FEATURES

- Water Repellency
- Efflorescence Control

BENEFITS

- Minimizes Water Penetration/Absorption
- Improves Service Life of CMUs
- Improves Aesthetic Appearance of CMUs
- Promotes and Maintains Brighter Colours

TECHNICAL INFORMATION

| Parameter | Typical Value |
|------------------|-----------------|
| Appearance | Clear Liquid |
| Specific Gravity | 0.900 |
| Solids, % | Not Established |
| IR | Pass |

DIRECTIONS FOR USE

1. Use at dosage rate 125 - 250ml per 100kg of cementitious material.
2. Add after the introduction of the pre-wet aggregates.
3. Mix for 90 seconds after addition of admixture.
4. Check the moisture content of the mix and add additional water if needed.

PRODUCT PACKAGING

Available in 1000 litre IBCs, 210 litre drums and 25 litre jerry cans. Samples are available by request.

PRODUCT STORAGE AND SHELF LIFE

Store in dry area. Keep containers tightly closed. Do not store in excessively high temperatures (>35 C°). KEEP FROM FREEZING. Avoid physical damage to containers.

Krete Control 230 has a rheological shelf life of eight (8) months in original, unopened packaging.

The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.

PDS - Control 230 - 01/2016

*For Industrial Use Only.
Not for internal consumption.
Consult SDS for safety and regulatory information.*

