

CONCRETE

PRODUCT DATA SHEET

Krete Mix 150

Krete Mix 150 is a concentrated, swipe producing admixture designed to offer plasticizing action in semi dry concrete products.

FEATURES

- Plasticizing Action
- Allows for More Water

BENEFITS

- Improves Batch Consistency
- Decreases Machine Feed Time
- Improves Green Strength
- Improves Finish Texture
- Effectively Hydrates Cement
- Improves Compressive Strength
- Provides Swipe

TECHNICAL INFORMATION

| Parameter | Typical Value |
|------------|-------------------|
| Appearance | Pale Green Liquid |
| Gravity | Specific 1.032 |
| pH | 9.50 |
| Solids, % | Not Established |
| IR | Pass |

DIRECTIONS FOR USE

1. Use at dosage rate of 125 - 175ml per 100kg of cementitious material.
2. Add with or after the main portion of batch water.

PRODUCT PACKAGING

Available in 1000 litre IBCs, 210 litre drums and 25 litre jerry cans. Samples are available by request.

PRODUCT STORAGE AND SHELF LIFE

Store in dry area. Keep containers tightly closed. Do not store in excessively high temperatures (>35 C°). KEEP FROM FREEZING. Avoid physical damage to containers.

Krete Mix 150 has a rheological shelf life of eight (8) months in original, unopened packaging.

The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.

PDS - Mix 150 - 01/2016

*For Industrial Use Only.
Not for internal consumption.
Consult SDS for safety and regulatory information.*

