

# CONCRETE

## PRODUCT DATA SHEET

### RT Form Oil

RT Form Oil is a mineral based release oil formulated for the roof tile industry to ensure early mould release once the concrete has set.

#### FEATURES

- Specially formulated for the roof tile industry
- Suitable for most mould types (except rubber and polystyrene)
- Ready to use product
- Will not clog fine jets

#### BENEFITS

- Consumption reduction in grams per roof tile pallet vs self-blended oils
- Temporarily protects metallic moulds from corrosion and extends the life of the mould
- Does not stain or affect the colour of the concrete
- Does not affect the adhesion of subsequent finishes and coatings
- Does not modify cement hydration

#### TECHNICAL INFORMATION

Parameter	Typical Value
Appearance	Amber Liquid
Specific Gravity	0.82 - 0.87
pH	5 (±1)
Flash Point	90°C
Viscosity (@25°C)	8 seconds (Ford #4 cup)

*The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.*

*For Industrial Use Only.  
Not for internal consumption.  
Consult SDS for safety and regulatory information.*

#### DIRECTIONS FOR USE

##### Before application

1. Mould must be stripped and cleaned of concrete and oil deposits.
2. RT Form Oil is usually applied by an in line high pressure oil sprayer or in line brush applicator.

##### After application

Avoid excessive application.

#### PRODUCT PACKAGING

Available in 1000 litre IBCs, 210 litre drums and 25 litre jerry cans.

#### PRODUCT STORAGE AND SHELF LIFE

RT Form Oil has a shelf life of up to 24 months in original, unopened packaging. Will thicken in winter. Should the product freeze, it will recover its properties after thawing and agitating. Avoid storing in direct sunlight.

PDS - RT Form Oil - 01/2016