

CONCRETE

PRODUCT DATA SHEET

Krete Mix 110

KreteMix 110 is an aqueous admixture designed to offer plasticizing action while allowing increased water use in semi dry concrete products.

FEATURES

- Plasticizing Action
- Allows Increased Water Use

BENEFITS

- Improves Batch Consistency
- Decreases Machine Feed Time
- Improves Green Strength
- Improves Finish Texture
- Effectively Hydrates Cement
- Improves Compressive Strength

TECHNICAL INFORMATION

Parameter	Typical Value
Appearance	Clear Blue Liquid
Specific Gravity	1.032
pH	7.20
IR	Pass

DIRECTIONS FOR USE

1. Use at dosage rate of 65 - 130ml per 100kg of cementitious material.
2. Add after the main portion of batch water.
3. Mix for 60 seconds after addition of admixture.

PRODUCT PACKAGING

Available in 1000 litre IBCs, 210 litre drums and 25 litre jerry cans. Samples are available by request.

PRODUCT STORAGE AND SHELF LIFE

Store in dry area. Keep containers tightly closed. Do not store in excessively high temperatures (>35 C°). KEEP FROM FREEZING. Avoid physical damage to containers.

KreteMix 110 has a rheological shelf life of eight (8) months in original, unopened packaging.

The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.

PDS - Mix 110 - 01/2016

*For Industrial Use Only.
Not for internal consumption.
Consult SDS for safety and regulatory information.*

